eSSL
Technology Development Company

SESS SAFEGUARD E-SECURITY SYSTEMS
more than just security

SC 405

Proximity T&A System with Access Control

Card Capacity : 30,000
Transaction Storage : 50,000
Card Reader : Yes
CPU : 32 bit High End Microprocessor
FAR : <=0.0001% / FRR : <=1%
Identication Speed : <=0.1 sec
Display : Black & White
Keypad : 4 x 4 Keypads
LED Indicator : Green/Red
Schedule Bell/Speaker : Mini Speaker
Communication : TCP/IP,USB,RS485
Power Supply : 12V DC, 2amps / 3amps
Operating Temprature : 0°C to 45°C
Operating Humidity : 20% -80%
Dimension : 143 x 95.5 x39.5mm
Access Control : Wiegand : In & Out
Relay : Inbuilt relay to communicate with Locks, Alarms & Door Sensors

Support Fire Alarm : Yes / Door Sensor ; Yes
Anti Passback : Yes / Door Bell : Yes
Support exit reader : KR 500E / Exit Button /
101 HE,50 time zones, 5 groups, 10 time combinations
Battery : No / Card Readers : Yes
Communication : No
Printer : No

Compatibility :
- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)

Compatible Software & SDK :
- Smart Office Suite Desktop
- etime tracklite Desktop & Web
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data. Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications

Safeguard E Security Systems
Old No.36/2, New No.12, V Block,11th Street, Anna Nagar,Chennai - 600 040.
Phone : 044 45576407 / 96000 76407. Email : admin@sesspl.in. Website : www.sesspl.in

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development
www.esslsecurity.com
FC CE RoHS